


DOORS


Visoglide



Horizontal Section



Vertical Section



Trade Name	Visoglide
Building applications	Designed for use as fixed lights and horizontal sliding doors internally beaded for domestic and all commercial applications
	Weight limit 200Kg. Height limit 2550mm
Special features	2, 3, 4 and 6 door panels available All applications are internally glazed with square beads Polyamide thermal break allowing dual colour option
Materials	Aluminium alloy 6060/6063 T5/T6 in condition F22 to NBN P21-001 and DIN 1725 Thermal break: polyamide strips PA 6.6. 25% reinforced with glass fibre Glazing seals: EPDM to DIN 7863, TV 110 NFP 85301, ISO 3994 Weatherseals: Woolpile
Finish	Polyester powder coat to BS 6496/APA-Qualicoat Guidelines. Anodised satin or bronze colours with EWAA/EURAS-Qualinod quality label Dual colour available
Profile width	Head, cill and jamb 116mm Mullion 83mm and bi-parting stiles 158mm
Depth of frame	Two track 99mm and three track 155mm
Glass	Glazing options from 4mm to 28mm
Sash inserts	Fixed lights and horizontal sliding panels
Performance	Weather tested in accordance with BS6375 Pts 1 Tested to NEN-norm 5096. Security tested by SKG Complies with Doc. L for thermal transmittance Test Reports are available on request

